

DHL49

49" FHD LCD Monitor



Features :

- Industrial level LCD panel, suitable for extensive 24/7 continuous works
- High fidelity digital processing, brilliant and vivid video
- Low response time, no picture ghosting
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Infrared, RS232 double mode, supporting remote PC control
- Using tamper-proof metal housing, stable and reliable
- Professional thermal design to extend equipment lifespan



Technical Specification

Model

Model	DHL49
-------	-------

System

Diagonal	49"(16:9)
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance (Standard)	450 cd/㎡
Contrast	1100:1
Angle of view	178°/178°(vertical/horizontal)
Response time	8ms
Display Color	8bit(16.7M)
VESA	300×300mm

Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RJ45(RS232)×1, USB×1
Output	CVBS(BNC)×2, RJ45(RS232)×1
Speaker	10W×2

General

Consumption (Standard)	60W
Consumption (Standby)	≤1W

Power Supply	AC100~240V (+/-10%), 50/60 Hz
Net Weight	19.5kg
Gross Weight	23.5kg
Dimensions(no base)	1127.1×667.3×52.9mm
Work Environment	Temperature: 0℃~50℃ Humidity: 20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Dimensions(mm)

