

# LM28-S400

## 28" UHD LED Monitor



### Features :

- Using tamper-proof metal housing
- 4K Ultra-HD resolution
- Built-in 3D COMB filter and 3D Noise Reduction
- 5ms fast response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Support multiple signals, such as VGA, BNC, DP, HDMI, USB multimedia, Audio



### Technical Specification

#### Model

Model	LM28-S400
-------	-----------

#### Display

Screen Size	28"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	300cd/㎡
Contrast	1000:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	170°(H)/160°(V)
Response time	5ms
Refresh Rate	60Hz

#### Signals

Input	VGA(D-Sub)×1, BNC×1, DP 1.2a×1, HDMI 2.0×2, USB multimedia×1, Audio×1	
Output	BNC×1	
	Speaker	5W×2

#### General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	40W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	6.65kg (14.7lb)	
Gross Weight	8kg (17.6lb)	
Bezel Width	19.1mm(U), 19.0mm(R/L), 27.2mm(B)	
VESA	100×100mm (3.9"×3.9")	
Dimension without standard (W×H×D)	662×390.5×50mm (26.1"×15.4"×2.0")	
Package(W×H×D)	755×490×129mm (29.7"×19.3"×5.1")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%~85%

#### Accessory

Standard	HDMI cable, power cable, hanging bracket, remote control
Optional	Pedestal

#### Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

